

DA 2628

Extractor unit

with energy-efficient LED lighting and light-touch switches for easy use.



- Customised kitchen design – fully integrated in 1180 mm width
- Unique user convenience – Con@ctivity
- Powerful – 640 m³/h in Booster level
- Energy-efficient and quiet – powerful ECO motor
- Elegant and efficient – edge extraction panels



EAN: 4002516001515 / Material number: 10851370 /
Old Material Number: 28262855GB

Construction type and design	
Appliance colour	Stainless steel
Construction type	
Integrated extractor	•
Operating modes	
Type of air guide	Exhaust air
Design	
Edge extraction	•
User convenience	
Miele@home	•
Automatic function Con@ctivity	•
Electronic controls	•
Controls	Light-touch switches with LEDs
Miele@mobile app	•
Power levels (number without Booster level)	3
Booster levels	1
Run-on time 5/15 min.	•
Grease filter saturation indicator	•
Efficiency and sustainability	
Annual energy consumption in kWh/year	26.8
Energy efficiency class (A+++ – D)	A+
ECO motor	•
Grease filtering efficiency class	A
ECO motor (DC motor)	•
PowerManagement system	•
Fluid dynamic efficiency class	A
Lighting efficiency class	A
Cleaning and care	
Easy-to-clean canopy interior – CleanCover	•
Filter system	
Number of dishwasher-safe stainless steel grease filters (10-ply)	4
Lighting	
Number x W	3 x 4,5 W
Light intensity in lx	700 lx
Colour temperature in K	3500 Kelvin
Dimmer function	•
Fan	
Dual-action blower	•
Exhaust air	
Air throughput in Level 1 (m ³ /h) according to EN 61591	200
Air throughput in Level 2 (m ³ /h) according to EN 61591	300
Air throughput in Level 3 (m ³ /h) according to EN 61591	400
Air throughput in Booster level 1 (m ³ /h) according to EN 61591	640
Sound power in Level 1 (dB(A) re 1 pW) according to EN 60704-3	36.0

DA 2628

Extractor unit

with energy-efficient LED lighting and light-touch switches for easy use.



EAN: 4002516001515 / Material number: 10851370 /

Old Material Number: 28262855GB

Sound power in Level 2 (dB(A) re 1 pW) according to EN 60704-3	44.0
--	------

Sound power in Level 3 (dB(A) re 1 pW) according to EN 60704-3	51.0
--	------

Sound power in Booster level (dB(A) re 1 pW) acc. to EN 60704-3	62.0
---	------

Sound pressure in Level 1 (dB(A) re 20 µPa) according to EN 60704-2-13	22.0
--	------

Sound pressure in Level 2 (dB(A) re 20 µPa) according to EN 60704-2-13	30.0
--	------

Sound pressure in Level 3 (dB(A) re 20 µPa) according to EN 60704-2-13	37.0
--	------

Sound power in Booster level (dB(A) re 20 µPa) acc. to EN 60704-2-13	48.0
--	------

Safety

Safety switch-off	•
-------------------	---

Technical data

Canopy width in mm	1180
--------------------	------

Canopy height in mm	63
---------------------	----

Canopy depth in mm	293
--------------------	-----

Net weight in kg	15.0
------------------	------

Length of supply lead in m	1.5
----------------------------	-----

Standard plug fitted	•
----------------------	---

Minimum height above electric hobs in mm	450
--	-----

Minimum safety distance above gas hobs (max. 12.6 kW total power, burner ≤ 4.5 kW) in mm	650
--	-----

Number of phases	1
------------------	---

Total rated load in kW	0.09
------------------------	------

Voltage in V	230
--------------	-----

Fuse rating in A	10
------------------	----

Frequency in Hz	50
-----------------	----

Installation notes

Extraction ducting connection at top	•
--------------------------------------	---

Extraction ducting connection at rear	•
---------------------------------------	---

Extraction connection at top and rear	•
---------------------------------------	---

Diameter of exhaust duct in mm	150
--------------------------------	-----

Combination with WiFi-enabled Miele hob	recommended
---	-------------

Accessories included

Non-return flap	•
-----------------	---