

for steam cooking, baking, roasting with networking + HydroClean.



- Large clear text display with sensor controls DirectSensor
- Perfect results DualSteam technology
- Crispy outside, succulent inside combination cooking
- Convenient operation water container behind automatic panel
- Easy cleaning HydroClean and stainless steel oven compartment



EAN: 4002516625209 / Material number: 12101320 / Old Material Number: 23746049GB

| Old Material Number: 23746049GB | |
|--|-----------------------------|
| Construction type and design | |
| Steam combination oven | • |
| PureLine | • |
| Appliance colour | Stainless steel/Clean Steel |
| Convenience features | |
| Rapid heat-up | • |
| Pre-heating | • |
| External steam generation | • |
| Oxygen sensor | • |
| Individual humidity settings in combination cooking | • |
| Menu cooking without transfer of taste | • |
| Prepare plated meals with "Mix & Match" | • |
| Automatic programmes with ability to make individual adjustments | • |
| Keeping warm | • |
| Crisp function | • |
| Operating modes | |
| Fan plus | • |
| Conventional heat | • |
| Steam cooking | • |
| Combination cooking | • |
| Combination cooking with Fan plus | • |
| Combination cooking with Conventional heat | • |
| Combination cooking with grill | • |
| Sous-vide | • |
| Intensive bake | • |
| Fan grill | • |
| Grill | • |
| Economy grill | • |
| Top heat | • |
| Bottom heat | • |
| Cake plus | • |
| Eco fan heat | • |
| Eco steam cooking | • |
| Defrost | • |
| Roast with moisture | • |
| Reheat | • |
| Plate warming | • |
| Automatic programmes | • |
| Country-specific automatic programmes | • |
| Special applications | • |
| User convenience | |
| Networking with Miele@home | • |
| Display | DirectSensor |
| SoftOpen | • |
| SoftClose | • |
| | |
| MultiLingua | • |



for steam cooking, baking, roasting with networking + $\mbox{\sc HydroClean}.$



| EAN: 4002516625209 / Material number: 12101320 / Old Material Number: 23746049GB | |
|--|------|
| | |
| Quantity-independent cooking | • |
| Steam cooking on up to 4 levels at the same time Automatic menu cooking | • |
| Steam reduction before end of programme | • |
| Time of day display | • |
| Date display | • |
| Minute minder | • |
| Programmable start of cooking duration | • |
| Programmable end of cooking duration | • |
| Programmable cooking duration | • |
| Actual temperature display | • |
| Target temperature display | • |
| Buzzer when desired temperature is reached | • |
| Recommended temperature | • |
| User programmes | • |
| Sabbath programme | • |
| Individual settings | • |
| Efficiency and sustainability | |
| Energy efficiency class (A+++ – D) | A+ |
| Power rating in off mode in W | 0.3 |
| Power rating in standby mode in W | 0.8 |
| Power rating in networked standby in W | 2.0 |
| Time until automatic switch to standby in min | 20 |
| Time until automatic switch to off mode in min | 20 |
| Time until automatic switch to networked standby in min | 20 |
| Cleaning and care | |
| Stainless steel/CleanSteel finish | • |
| Stainless-steel oven compartment with linen structure | • |
| Hinged grill element | • |
| External steam generator | • |
| HydroClean | • |
| Soak programme | • |
| Rinse programme | • |
| Oven compartment drying programme | • |
| Quick-release side racks | • |
| Removable stainless-steel side racks | • |
| Automatic descaling | • |
| CleanGlass door | • |
| Steam techn./water supply | |
| DualSteam | • |
| Steam generator power in kW | 3.30 |
| Fresh water container volume in I | 1.4 |
| Fresh water container behind motorised control panel | • |
| Condensate container behind motorised lift-up control | • |
| panel with SoftClose | |
| Drain filter | • |
| Safety | |
| Appliance cooling system and touch-cool front | • |
| Safety switch-off | • |
| | |



for steam cooking, baking, roasting with networking + HydroClean.



| System lock | • |
|---|-------------------------|
| Vapour cooling system | • |
| Sensor lock | • |
| Technical data | |
| Oven compartment volume in l | 67 |
| No. of shelf levels | 4 |
| Appliance dimensions (W x H x D) in mm | 595 x 596 x 567 |
| Numbered shelf levels | • |
| Door hinge | Bottom |
| Oven light | BrilliantLight |
| Oven temperature regulation min. in °C | 30 |
| Oven temperature regulation max. in °C | 230 |
| Electronic steam oven temperature regulation min. in °C | 40 |
| Electronic steam oven temperature regulation max. in °C | 100 |
| Niche width min. in mm | 560 |
| Niche width max. in mm | 568 |
| Niche height min. in mm | 590 |
| Niche height max. in mm | 595 |
| Niche depth in mm | 550 |
| Appliance width in mm | 595 |
| Appliance height in mm | 596 |
| Appliance depth in mm | 567 |
| Weight in kg | 46.4 |
| Total rated load in kW | 3.45 |
| Voltage in V | 230 |
| Frequency in Hz | 50 |
| Fuse rating in A | 16 |
| Number of phases | 1 |
| Mains cable with plug | • |
| Length of supply lead in m | 2 |
| Replacing lamps | Service |
| Accessories included | |
| Universal tray with PerfectClean HUBB 71 | 1 |
| Baking and roasting rack with PerfectClean HBBR 71 | 1 |
| Removable side runners (pair) | 1 |
| Perforated stainless-steel cooking containers | 1 |
| Solid stainless steel cooking containers | _ 1 |
| HydroClean cleaning agent | 1 |
| Descaling tablets | 2 |
| Available display languages | |
| Available display languages via MultiLingua | bahasa malaysia, dansk, |




for steam cooking, baking, roasting with networking + HydroClean.


Míele

DGC 7460 HC Pro


for steam cooking, baking, roasting with networking + HydroClean.




H7000 handle, installation drawing
1) 400 mm, 2) 360 mm, 3) 47 mm, 4) 24 mm, 5)




Installation DGC XXL, ESW7x20 installation drawings




Installation_DGC_XXL_ESW7x10_EVS7010 installation drawings




built-in DGC XXL, installation drawing




built-in DGC XXL build-under, installation drawing
Worktop overhang ≤ 29 mm




screw joint DGC XXL, installation drawing



 ${\tt DGC7x4x}$ swivel range of the aperture, installation drawings



side view DGC XXL, installation drawings



Seitenansicht DGC XXL, installation drawing, GB, AU 22 mm glass, 23,3 mm stainless steel